15000 liter tank i Rostfritt 304



146 000 SEK /st exkl moms

Additional information: Struts between the feet made of mild steel (see photos); some residues of previous content
Volumetric volume (L): 15.000 L
Pressure in tank: pressure
Max. pressure (Bar): 1 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 25 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 30 L
Max Overpressure: 2 Bar

Max. working temperature: 3 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: cylinder
Outlet of tank: DN80 DIN 11851
Cylinder: 3,50 mm
Bottom: 3,40 mm

Internal diameter tank: 2.200 mm
Cylinder height: 3.360 mm
Total height of tank: 5.900 mm

SKU: 458492

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 25 °C
Mobil tank: Nej
Övrig information: Brewery; Struts between the feet made of mild steel (see photos); some residues of previous content
Omrörare: Nej
Övertryck: 1 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 15000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.360 mm
Invändig diameter: 2.200 mm
Total höjd: 5.900 mm

Tjocklek på tank
Botten: 3,40 mm
Cylinder: 3,50 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se