

15000 liter tank i Rostfritt 304



146 000 SEK /st exkl moms

Additional information: Brewery; Struts between the feet made of mild steel (see photos); some residues of previous content

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmosferic

Max. pressure (Bar): 1 Bar

Max. temperature (°C): 25 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 30 L

Max Overpressure: 2 Bar

Max. working temperature: 3 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: DN80 DIN 11851

Cylinder: 3,50 mm

Bottom: 3,40 mm

Internal diameter tank: 2.200 mm

Cylinder height: 3.360 mm

Total height of tank: 5.900 mm

SKU: 458492

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 25 °C

Mobil tank: Nej

Övrig information: Brewery; Struts between the feet made of mild steel (see photos); some residues of previous content

Omrörare: Nej

Övertryck: 1 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 15000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.360 mm

Invändig diameter: 2.200 mm

Total höjd: 5.900 mm

Tjocklek på tank

Botten: 3,40 mm

Cylinder: 3,50 mm

Mer

Isolerad: Nej