15000 liter tank i Rostfritt 304 (dubbelmantlad)



190 000 SEK /st exkl moms

Additional information: Safety double jacket made of stainless steel 304 around the vessel; various technical documents (in French and English); manhole DN 500 with dip pipes; tanks with (sometimes stronger) dents in the double jacket (in one tank also in the inner tank; see photos); connections for safety double jacket waved off.
Volumetric volume (L): 15.000 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: horizontal

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: non-existent
Cylinder: 6 mm
Bottom: 5,30 mm
Internal diameter tank: 2.200 mm
Outer diameter tank: 2.350 mm

Total outer length: 4.460 mm

SKU: 458636

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Safety jacket, Aisi 304 around the tank; Various technical documents (in French or English); Manhole DN 500 with dip tubes; Tanks with (sometimes stronger) dents in the safety jacket (in the case of
Övrig information2: 1 tank also in the inner tank; see photos); Connections for safety jacket cut off
Omrörare: Nej
Total urtappning: Nej
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 15000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 2.200 mm
Ytterdiameter: 2.350 mm

Tjocklek på tank

Botten: 5,30 mm
Cylinder: 6 mm

Mer
Isolerad: Nej