

## 15000 liter tank i Rostfritt 304



**190,000,00 kr /st exkl moms**

**Additional information:** Safety jacket, Aisi 304 around the tank; Various technical documents (in French or English); Manhole DN 500 with dip tubes; Tanks with (sometimes stronger) dents in the safety jacket (in the case of 1 tank also in the inner tank; see photos); Connections for safety jacket cut off

**Volumetric volume (L):** 15.000 L

**Pressure in tank:** ATM - atmosferic  
**Material wet parts:** SS AISI 304 (V2A)  
**Model:** horizontal

**Configuration:** single-skin  
**Heat exchanger:** no  
**Insulation:** no  
**Mobile tank:** no  
**Total discharge:** no

**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no  
**Position of manway:** headside

**Outlet of tank:** non-existent  
**Cylinder:** 6 mm  
**Bottom:** 5,30 mm  
**Internal diameter tank:** 2.200 mm  
**Outer diameter tank:** 2.350 mm

**Total outer length:** 4.460 mm

**SKU:** 458636

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Safety jacket, Aisi 304 around the tank; Various technical documents (in French or English); Manhole DN 500 with dip tubes; Tanks with (sometimes stronger) dents in the safety jacket (in the case of

Övrig information2: 1 tank also in the inner tank; see photos); Connections for safety jacket cut off

Omrörare: Nej

Total urtappning: Nej

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 15000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Invändig diameter: 2.200 mm

Ytterdiameter: 2.350 mm

## Tjocklek på tank

Botten: 5,30 mm

Cylinder: 6 mm

**Mer**

Isolerad: Nej

---