

## 15000 liter tank i Rostfritt 304



**201,000,00 kr /st exkl moms**

**Additional information:** Food; Double jacket with trickle ring - only suitable for unpressurized tempering

**Volumetric volume (L):** 15.000 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,50 Bar



**Min. pressure (Bar):** 0,80 Bar

**Max. temperature (°C):** 145 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** flange DN65

**Agitator:** yes

**Number of revolutions:** 145

**Power:** 3

**Top:** 10 mm

**Cylinder:** 8 mm

**Bottom:** 10 mm

**Internal diameter tank:** 2.300 mm

**Cylinder height:** 3.250 mm

**Total height of tank:** 5.100 mm

**Empty weight tank:** 3.000

**SKU:** 568142

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: Food; Double jacket with trickle ring – only suitable for unpressurized tempering; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,80 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 15000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304



## Dimensioner av tank

Cylinderhöjd: 3.250 mm  
Invändig diameter: 2.300 mm  
Total höjd: 5.100 mm

## Omrörare

Kraft (kW): 3  
Varvtal: 145

## Tjocklek på tank

Botten: 10 mm  
Cylinder: 8 mm  
Topp: 10 mm

## Mer

Isolerad: Ja  
Vikt: 3.000