

## 15000 liter tank i Rostfritt 304



**118,000,00 kr /st exkl moms**

**Additional information:** Rennet production; Manhole diameter approx. 415 mm; tank with adhesions inside; slight corrosion on the inside and outside of the tank; dents at the insulation jacket

**Volumetric volume (L):** 15.000 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Number of revolutions:** 1.420

**Power:** 3

**Internal diameter tank:** 2.490 mm

**Outer diameter tank:** 2.600 mm

**Cylinder height:** 2.900 mm

**Total height of tank:** 4.700 mm

**SKU:** 280168

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Rennet production; Manhole diameter approx. 415 mm; tank with adhesions inside; slight corrosion on the inside and outside of the tank; dents at the insulation jacket; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 15000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 2.900 mm

Invändig diameter: 2.490 mm

Total höjd: 4.700 mm

Ytterdiameter: 2.600 mm

**Omrörare**

Kraft (kW): 3

Varvtal: 1.420

**Mer**

Isolerad: Ja