

## 15000 liter tank i Rostfritt 304



**143,000,00 kr /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** we can't give any guarantees about the agitator

**Volumetric volume (L):** 15.000 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no



**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** dished

**Total discharge:** yes

**Fixation points:** 4 non adjustable feet

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Suitable for food industry:** no

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** headside

**Hinged lid:** yes

**Tank outlet:** inside Ø 60 mm

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** at the top

**Number of revolutions:** 25

**Power:** 4

**Voltage:** 380 V - three-phase

**Distance from outlet to ground:** 120 mm

**Outer diameter tank:** 2.300 mm

**Cylinder height:** 2.700 mm

**Total height of tank:** 4.350 mm

**Empty weight tank:** 900

**SKU:** 485924

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 15000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Tankutlopp: inside Ø 60 mm

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304



## Dimensioner av tank

Cylinderhöjd: 2.700 mm

Mått utlopp till marcken: 120 mm

Total höjd: 4.350 mm

Ytterdiameter: 2.300 mm

## Omrörare

Kraft (kW): 4

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 25

Spänning (Volt): 380 V – three-phase

## Mer

Isolerad: Nej

Vikt: 900