

15000 liter tank i Rostfritt 304



285,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: ex chocolate tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 15.000 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C



Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical 20

Shape of tank: cylindrical

Bottom type: conical 20

Total discharge: yes

Fixation points: 3 non adjustable feet

Type of HE on the bottom: dimple-jacket

Water pressure HE: 4 Bar

Hydraulic test pressure: 5 Bar

Working temperature HE bottom: 70 °C

Heat exchanger: RVS 304

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304L

Fixation point(s): RVS 304L

Wet parts agitator(s): SS AISI 304L (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 600 mm

Tank outlet: inside Ø 100 mm

Agitator: yes

Agitator type: gate

Position engine: at the top

Number of revolutions: 12
Power: 5,50
Voltage: 380 V - three-phase
Top: 5 mm

Cylinder: 3 mm
Bottom: 4 mm
Insulation body: yes
Insulation bottom/sides: yes
Insulation thickness: 80

Internal diameter tank: 2.750 mm
Distance from outlet to ground: 930 mm
Outer diameter tank: 2.950 mm
Cylinder height: 2.280 mm
Total height of tank: 5.300 mm

Empty weight tank: 3.500

SKU: 482790

Mer information
