

## 15000 liter tank i Syrafast 316



**59,000,00 kr /st exkl moms**

**Article type:** second-hand storage tank

**Additional information:**

*The tank is dented at the top (see photos). The attached technical drawing shows how the tank was originally built, the previous customer has made some adjustments, look carefully at the photos.*

**Volumetric volume (L):** 15.000 L

**Max. density P (kg/m<sup>3</sup>):** 1.150

**Ra inner weld:** 1,60

**Finish stainless steel:** 2B

**Pressure in tank:** ATM - atmosferic  
**Material wet parts:** SS AISI 316 (V4A)  
**Model:** vertical  
**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes  
**Insulation:** no  
**Mobile tank:** no  
**Top type:** conical  
**Shape of tank:** cylindrical

**Bottom type:** conical 15 °  
**Bottom outlet:** yes  
**Total discharge:** yes  
**Fixation points:** 4 adjustable feet  
**Type of HE on the cylinder:** heating/cooling jacket

**Position HE:** the middle part of the cilinder  
**Number of sections:** 1  
**with windings:** 7  
**Water pressure HE:** 2,50 Bar  
**Steam pressure HE:** 0,49 Bar

**Contact surface cylinder:** 5,80 m<sup>2</sup>  
**Connection HE:** 1 INCH BSP  
**Working temperature HE cylinder:** 100 °C  
**Heat exchanger:** RVS 304  
**Manway(s):** RVS 316

**Gasket manway(s):** EPDM  
**Fixation point(s):** RVS 304L  
**Suitable for food industry:** yes  
**Documents included:** yes, optional  
**Technical drawing included:** yes

**Registration plate on the tank:** no  
**Flange for agitator:** no  
**Number of manways:** 1  
**Position of manway:** at the top

**Hinged lid:** yes

**Tank outlet:** inside Ø 65 mm

**Tank location:** outside

**Agitator:** no

**Top:** 2 mm

**Cylinder:** 2 mm

**Bottom:** 2,50 mm

**Internal diameter tank:** 2.359 mm

**Distance from outlet to ground:** 200 mm

**Outer diameter tank:** 2.410 mm

**Cylinder height:** 3.250 mm

**Total height of tank:** 4.400 mm

**Empty weight tank:** 850

**SKU:** 299700

---

Mer information

---