

15000 liter tank i Syrafast 316



141 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The tank only had 1 testrun with water, the production has never started.; we can't give any guarantees about the agitator

Volumetric volume (L): 15.000 L

Max. density P (kg/m³): 1.000

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 10 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 4 adjustable feet

Manway(s): RVS 316

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 316 (V4A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Tank outlet: inside Ø 65 mm

Total outlet valve: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Power: 0,75

Voltage: three-phase

Outer diameter tank: 2.240 mm

Cylinder height: 3.750 mm

Total height of tank: 4.850 mm

Empty weight tank: 850

SKU: 488568

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Maximal densitet för produkten: 1000

Mobil tank: Nej

Övrig information: The tank only had 1 testrun with water, the production has never started.; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 15 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 15000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 65 mm
Teknisk ritning finns: Nej
Utloppsventil: Ja

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Material vätskeberörd del på omrörare: SS AISI 316 (V4A)

Dimensioner av tank

Cylinderhöjd: 3.750 mm
Total höjd: 4.850 mm
Ytterdiameter: 2.240 mm

Omrörare

Kraft (kW): 0,75
Position motor: in the cylinder
Typ av omrörare: propeller agitator
Spänning (Volt): three-phase

Mer

Isolerad: Nej
Vikt: 850