15500 liter tank i Rostfritt 304



132 000 SEK /st exkl moms

Additional information: bioenergy; bearing shells cut-off below; 1 manhole diameter 430 mm in the front bottom; former connections welded closed; dents at the cylinder
Volumetric volume (L): 15.500 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: horizontal

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Outlet of tank: 50

Cylinder: 2,50 mm
Bottom: 2,50 mm
Internal diameter tank: 2.000 mm
Total height of tank: 2.650 mm
Total outer length: 5.450 mm

Empty weight tank: 1.000

SKU: 409733

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: bioenergy; bearing shells cut-off below; 1 manhole diameter 430 mm in the front bottom; former connections welded closed; dents at the cylinder
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 15500

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 2.000 mm
Total höjd: 2.650 mm

Tjocklek på tank

Botten: 2,50 mm
Cylinder: 2,50 mm

Mer
Isolerad: Nej
Vikt: 1.000