

1575 liter tank i Syrafast 316



196 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; Manhole DN 350/450 (sight glass in the manhole cover is missing); support ring, Fe; Flanges partly made of Fe

Volumetric volume (L): 1.575 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 55 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 130

Agitator: yes

Number of revolutions: 10 - 50

Power: 5,50

Top: 7,10 mm

Internal diameter tank: 1.200 mm

Cylinder height: 1.030 mm

Total height of tank: 3.500 mm

SKU: 290463

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; Manhole DN 350/450 (sight glass in the manhole cover is missing); support ring, Fe; Flanges partly made of Fe; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1575

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.030 mm
Invändig diameter: 1.200 mm
Total höjd: 3.500 mm

Omrörare

Kraft (kW): 5,50
Varvtal: 10 – 50

Tjocklek på tank

Topp: 7,10 mm

Mer

Isolerad: Nej