1600 liter tank i Rostfritt 304



51 000 SEK /st exkl moms

Additional information: Double jacket around the lower cylinder area and the lower base; manhole diameter approx. 415 mm; some residues of previous content
Volumetric volume (L): 1.600 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Outlet of tank: DN80 DIN 11851
Internal diameter tank: 1.190 mm
Outer diameter tank: 1.360 mm

Cylinder height: 1.450 mm
Total height of tank: 2.600 mm

SKU: 399140

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: Double jacket around the lower cylinder area and the lower bottom; Manhole diameter approx. 415 mm ; some residues of previous content
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1600

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.450 mm
Invändig diameter: 1.190 mm
Total höjd: 2.600 mm
Ytterdiameter: 1.360 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej