

## 1600 liter tank i Syrafast 316



**80 000 SEK /st exkl moms**

**Additional information:** Pharmaceutical Chemistry; 4 feet VA, screwed to 4 brackets VA; manhole DN 400; slight metallic discoloration inside; further technical documentation available; bump at the insulation jacket; manhole cover is missing

**Volumetric volume (L):** 1.600 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 2 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 95 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** horizontal

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** flange DN65

**Cylinder:** 4 mm

**Bottom:** 4 mm

**Internal diameter tank:** 900 mm

**Outer diameter tank:** 1.060 mm

**Total height of tank:** 2.100 mm

**Total outer length:** 2.700 mm

**SKU:** 293422

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; 4 feet, stainless steel, screwed to 4 support brackets, stainless steel; Manhole DN 400; slight metallic discoloration inside; further technical documents available ; bump

Övrig information2: at the insulation jacket;manhole cover is missing

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1600

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Invändig diameter: 900 mm

Total höjd: 2.100 mm

Ytterdiameter: 1.060 mm

## Tjocklek på tank

Botten: 4 mm

Cylinder: 4 mm

## Mer

Isolerad: Ja