

1600 liter tank i Syrafast 316



36 000 SEK /st exkl moms

Additional information: Chemistry; Tank designed for 3 bar operating pressure (however, the last operator used it without pressure and therefore re-stamped it by the TÜV to +0.5 bar operating pressure); 1 fitting flanged to the outlet; 1 pipe inside the tank; some residues of previous content; manhole cover plated

Volumetric volume (L): 1.600 L

Pressure in tank: pressure
Max. pressure (Bar): 3 Bar
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: in the bottom
Outlet of tank: flange DN50
Internal diameter tank: 1.000 mm
Cylinder height: 2.070 mm
Total height of tank: 3.200 mm

Empty weight tank: 770

SKU: 439778

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Chemistry; Tank designed for 3 bar operating pressure (however, the last operator used it without pressure and therefore re-stamped it by the TÜV to +0.5 bar operating pressure); 1 fitting flanged

Övrig information2: to the outlet; 1 pipe inside the tank; some residues of previous content; manhole cover plated

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1600

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.070 mm

Invändig diameter: 1.000 mm

Total höjd: 3.200 mm

Mer

Isolerad: Nej

Vikt: 770