1600 liter tank i Syrafast 316



61 000 SEK /st exkl moms

Additional information: 2 loose bearing shells made of stainless steel 304; DN 500 manhole; the exterior of the tank was sandblasted; 1 dent in the cylinder
Volumetric volume (L): 1.600 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: horizontal

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: flange DN50
Cylinder: 5 mm
Bottom: 3,90 mm
Internal diameter tank: 990 mm
Total height of tank: 1.700 mm

Total outer length: 2.550 mm

SKU: 483326

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: 2 loose bearing shells, Aisi 304; manhole DN 500
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1600

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 990 mm
Total höjd: 1.700 mm

Tjocklek på tank

Botten: 3,90 mm
Cylinder: 5 mm

Mer

Isolerad: Nej