

## 1600 liter tank i Syrafast 316



**139,000,00 SEK /st exkl moms**

**Additional information:** Biotech; 4 feet bolted to height-adjustable stainless steel weighing pallet; hand hole DN 200; an identical second vessel can be offered on request

**Volumetric volume (L):** 1.600 L

**Pressure in tank:** pressure and vacuum



**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 160 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 70 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 160 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 19 - 150

**Power:** 2,50

**Top:** 5,30 mm

**Cylinder:** 6 mm

**Bottom:** 7,20 mm

**Internal diameter tank:** 1.200 mm

**Outer diameter tank:** 1.364 mm

**Cylinder height:** 1.296 mm

**Total height of tank:** 3.850 mm

**SKU:** 570590

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 160 °C

Mobil tank: Nej

Övrig information: Biotech; 4 feet bolted to height-adjustable stainless steel weighing pallet; hand hole DN 200; an identical second vessel can be offered on request; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1600

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.296 mm  
Invändig diameter: 1.200 mm  
Total höjd: 3.850 mm  
Ytterdiameter: 1.364 mm

## Omrörare

Kraft (kW): 2,50  
Varvtal: 19 - 150

## Tjocklek på tank

Botten: 7,20 mm  
Cylinder: 6 mm  
Topp: 5,30 mm

## Mer

Isolerad: Ja