

16000 liter tank i Syrafast 316



257,000,00 kr /st exkl moms

Additional information: Chemistry; Suspended design on 4 feet, Fe (Caution: heating connections extend beyond the foot ends; foot ends were screwed to a working platform); manhole cover is missing

Volumetric volume (L): 16.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 490 L

Max Overpressure: 16 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 180

Agitator: yes

Number of revolutions: 30 / 46

Power: 15

Internal diameter tank: 2.800 mm

Cylinder height: 2.650 mm

Total height of tank: 5.350 mm

SKU: 298234

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Suspended design on 4 feet, Fe (Caution: heating connections extend beyond the foot ends; foot ends were screwed to a working platform); manhole cover is missing; we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 16000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.650 mm

Invändig diameter: 2.800 mm

Total höjd: 5.350 mm

Omrörare

Kraft (kW): 15

Varvtal: 30 / 46

Mer

Isolerad: Nej