# 16000 liter tank i Syrafast 316

263 000 SEK /st exkl moms

**Additional information**: Chemistry; Suspended design on 4 feet, Fe (Caution: heating connections extend beyond the foot ends; foot ends were screwed to a working platform); manhole cover is missing
**Volumetric volume (L)**: 16.000 L
**Pressure in tank**: pressure and vacuum
**Max. pressure (Bar)**: 2 Bar
**Min. pressure (Bar)**: 1 Bar

**Max. temperature (°C)**: 200 °C
**Material wet parts**: SS AISI 316 (V4A)
**Model**: vertical
**Configuration**: single jacketed with heat-exchanger
**Heat exchanger**: yes

**Insulation**: no
**Mobile tank**: no
**Total discharge**: yes
**Volume**: 490 L
**Max Overpressure**: 16 Bar

**Max. working temperature**: 200 °C
**Type HE on the bottom**: half pipe welded onto the outside of the innertank
**Type HE on the cylinder**: half pipe welded onto the outside of the innertank
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: yes
**Flange for agitator**: no
**Position of manway**: in the bottom
**Outlet of tank**: 180

**Agitator**: yes

**Number of revolutions**: 30 / 46
**Power**: 15
**Internal diameter tank**: 2.800 mm
**Cylinder height**: 2.650 mm
**Total height of tank**: 5.350 mm

**SKU:** 419735

## Mer information

## Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Chemistry; Suspended design on 4 feet, Fe (Caution: heating connections extend beyond the foot ends; foot ends were screwed to a working platform); manhole cover is missing; we can’t give any
Övrig information2: guarantees about the agitator
Omrörare: Ja
Övertryck: 2 Bar
Total urtappning: Yes
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 16000

## Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 2.650 mm
Invändig diameter: 2.800 mm
Total höjd: 5.350 mm

**Omrörare**
Kraft (kW): 15
Varvtal: 30 / 46

**Mer**
Isolerad: Nej