16150 liter tank i Syrafast 316



PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

244 000 SEK /st exkl moms

Additional information: Double jacket with trickle ring - only suitable for unpressurized tempering; in some cases, the welding of the double jackets has become slightly loose in the upper area; on request - up to 5x more vessels available (external storage)
Volumetric volume (L): 16.150 L
Pressure in tank: pressure
Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 3,20 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 1.000 L
Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outlet of tank: 80
Agitator: yes
Number of revolutions: 720 / 1460

Power: 1.7 / 6.8
Cylinder: 8 mm
Bottom: 6 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Internal diameter tank: 2.490 mm
Outer diameter tank: 2.580 mm

Cylinder height: 2.500 mm
Total height of tank: 5.000 mm

SKU: 435479

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Dairy; Double jacket with trickle ring – only suitable for unpressurized tempering; in some cases, the welding of the double jackets has become slightly loose in the upper area; on request – up to
Övrig information2: 5x more vessels available (external storage); we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 3,20 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 16150

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 2.500 mm
Invändig diameter: 2.490 mm
Total höjd: 5.000 mm
Ytterdiameter: 2.580 mm

Omrörare
Kraft (kW): 1.7 / 6.8
Varvtal: 720 / 1460

Tjocklek på tank
Botten: 6 mm
Cylinder: 8 mm

Mer
Isolerad: Nej