16300 liter tank i Rostfritt 304



244 000 SEK /st exkl moms

Article type: second-hand pressure tank
Volumetric volume (L): 16.300 L
Pressure in tank: vacuum
Max. pressure (Bar): 0,50 Bar
Min. pressure (Bar): -1 Bar

Max. temperature (°C): 50 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 304L (V2A)
Model: horizontal
Configuration: single-skin

Heat exchanger: no
Insulation: no
Mobile tank: no
Shape of tank: cylindrical
Wall type: dished

Total discharge: yes
Fixation points: 2 saddles
Fixation point(s): painted steel
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no
Tank outlet: inside Ø 100 mm
Internal diameter tank: 1.800 mm

Outer diameter tank: 2.000 mm
Cylinder height: 6.000 mm
Empty weight tank: 2.800

SKU: 479195

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 50 °C
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Omrörare: Nej
Övertryck: 0,50 Bar
Tankens form: cylindrical
Total urtappning: Yes
Undertryck (vakuum): -1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304L (V2A)
Volym i liter: 16300

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 100 mm
Teknisk ritning finns: Ja

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): painted steel

Dimensioner av tank

Cylinderhöjd: 6.000 mm
Invändig diameter: 1.800 mm
Ytterdiameter: 2.000 mm

Mer
Isolerad: Nej
Vikt: 2.800

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se