1660 liter tank i Syrafast 316



172 000 SEK /st exkl moms

Additional information: Liquid soap; System drawing available; vessel in the photo is the larger, left-hand tank at the previous operator; vessel was part of a process plant (the smaller tank in the photo is also available under order no. 9787 (subject to sale elsewhere))
Volumetric volume (L): 1.660 L
Pressure in tank: pressure

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 165 L
Max Overpressure: 6 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: 100
Agitator: yes
Number of revolutions: 8,2 - 26,5
Power: 7,50
Cylinder: 10 mm

Bottom: 8 mm
Internal diameter tank: 1.180 mm
Outer diameter tank: 1.360 mm
Cylinder height: 1.390 mm
Total height of tank: 3.200 mm

SKU: 479118

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Liquid soap; System drawing available; tank is the larger, left tank in the photo of the previous operator; tank was part of a process plant (the smaller tank in the photo is also available under
Övrig information2: order number 9787 (subject to sale elsewhere); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1660

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.390 mm
Invändig diameter: 1.180 mm
Total höjd: 3.200 mm
Ytterdiameter: 1.360 mm

Omrörare
Kraft (kW): 7,50
Varvtal: 8,2 – 26,5

Tjocklek på tank
Botten: 8 mm
Cylinder: 10 mm

Mer
Isolerad: Ja