

1690 liter tank i Syrafast 316



101 000 SEK /st exkl moms

Additional information: 2 bearing shells, stainless steel 316, bolted to a stainless steel 304 frame component; DN 500 manhole; insulation jacket with small dents; the insulation jacket has come loose slightly in places

Volumetric volume (L): 1.690 L



Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: horizontal

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 42

Internal diameter tank: 1.088 mm

Outer diameter tank: 1.230 mm

Total height of tank: 1.900 mm

Total outer length: 2.500 mm

SKU: 704659

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: insulated

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: 2 bearing shells, stainless steel 316, bolted to a stainless steel 304 frame component; DN 500 manhole; insulation jacket with small dents; the insulation jacket has come loose slightly in places

Omrörare: Nej

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1690

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.088 mm

Total höjd: 1.900 mm

Ytterdiameter: 1.230 mm



Mer

Isolerad: Ja