

1700 liter tank i Rostfritt 304



69,000,00 kr /st exkl moms

Additional information: Food industry; Operating pressure in the double jacket: 2.8 bar; 2 former connections in the upper bottom were welded shut by the previous operator

Volumetric volume (L): 1.700 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 210 L

Max Overpressure: 2,50 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 72

Power: 1,50

Internal diameter tank: 1.330 mm

Outer diameter tank: 1.420 mm

Cylinder height: 1.200 mm

Total height of tank: 3.300 mm

SKU: 304382

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Food industry; Operating pressure in the double jacket: 2.8 bar; 2 former connections in the upper bottom were welded shut by the previous operator; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1700

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.200 mm

Invändig diameter: 1.330 mm

Total höjd: 3.300 mm

Ytterdiameter: 1.420 mm

Omrörare

Kraft (kW): 1,50

Varvtal: 72

Mer

Värmeväxlare: RVS 304

Isolerad: Nej