1700 liter tank i Syrafast 316



231 000 SEK /st exkl moms

Volumetric volume (L): 1.700 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar
Min. pressure (Bar): 1 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no
Total discharge: no
Volume: 230 L
Max Overpressure: 8 Bar
Max. working temperature: 100 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Agitator: yes
Internal diameter tank: 1.170 mm
Outer diameter tank: 1.400 mm

Cylinder height: 1.170 mm
Total height of tank: 3.250 mm

SKU: 424049

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: pharmacy; we can’t give any guarantees about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 4 Bar
Total urtappning: Nej
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1700

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.170 mm
Invändig diameter: 1.170 mm
Total höjd: 3.250 mm
Ytterdiameter: 1.400 mm

Mer
Isolerad: Ja