17200 liter tank i Rostfritt 304



155 000 SEK /st exkl moms

Additional information: Oil/Margarine; Dimensions as shown in the drawing
Volumetric volume (L): 17.200 L
Pressure in tank: pressure
Max. pressure (Bar): 0,51 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no
Total discharge: yes
Volume: 33 L
Max Overpressure: 6 Bar
Max. working temperature: 100 °C

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: flange DN65
Agitator: yes
Number of revolutions: 60
Power: 3
Top: 4 mm

Cylinder: 3 mm
Bottom: 8,50 mm
Internal diameter tank: 2.098 mm
Cylinder height: 4.500 mm
Total height of tank: 5.891 mm

Empty weight tank: 1.500

SKU: 741943

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Oil/Margarine; Dimensions as shown in the drawing; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 0,51 Bar
Total urtappning: Ja
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 17200

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 4.500 mm
Invändig diameter: 2.098 mm
Total höjd: 5.891 mm

Omrörare
Kraft (kW): 3
Varvtal: 60

Tjocklek på tank
Botten: 8,50 mm
Cylinder: 3 mm
Topp: 4 mm

Mer
Isolerad: Ja
Vikt: 1.500