

17200 liter tank i Syrafast 316



266 000 SEK /st exkl moms

Additional information: Chemistry; 4 support brackets, Aisi 316; Pitting corrosion on the inside of the tank;
Metallic discolouration inside

Volumetric volume (L): 17.200 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 43 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN150

Agitator: yes

Power: 11

Top: 14,10 mm

Cylinder: 10 mm

Bottom: 10,10 mm

Internal diameter tank: 2.400 mm

Cylinder height: 3.250 mm

Total height of tank: 6.250 mm

SKU: 286553

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; 4 support brackets, Aisi 316; Pitting corrosion on the inside of the tank; Metallic discolouration inside; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 17200

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 3.250 mm

Invändig diameter: 2.400 mm

Total höjd: 6.250 mm

Omrörare

Kraft (kW): 11

Tjocklek på tank

Botten: 10,10 mm

Cylinder: 10 mm

Topp: 14,10 mm

Mer

Isolerad: Nej