


17360 liter tank i Syrafast 316



333 000 SEK /st exkl moms

Additional information: tank is unused, was only filled with demineralised water for pressure testing

Volumetric volume (L): 17.360 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN125 DIN 11851

Internal diameter tank: 2.000 mm

Cylinder height: 4.935 mm

Total height of tank: 5.800 mm

SKU: 313199

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: tank is unused, was only filled with demineralised water for pressure testing

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 17360

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.935 mm

Invändig diameter: 2.000 mm

Total höjd: 5.800 mm

Mer

Isolerad: Ja
