1750 liter tank i Syrafast 316



56 000 SEK /st exkl moms

Additional information: food colours; Cylinder can only be heated in the lower area; 1 distillation column/ heat exchanger made of stainless steel 304 is included in the scope of delivery (see photos; not included in the total height); some residues of previous content; bump at the insulation jacket; manhole cover plated
Volumetric volume (L): 1.750 L
Pressure in tank: pressure and vacuum

Min. pressure (Bar): 1 Bar
Max. temperature (°C): 160 °C

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no
Total discharge: yes
Volume: 139 L
Max Overpressure: 15,40 Bar
Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN150
Agitator: yes
Power: 7.5 / 9

Cylinder: 6 mm
Bottom: 6 mm
Internal diameter tank: 1.290 mm
Outer diameter tank: 1.540 mm
Cylinder height: 1.000 mm

Total height of tank: 3.450 mm

SKU: 395225

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 160 °C
Mobil tank: Nej
Övrig information: food colours; cylinder can only be heated in the lower area; 1 distillation column / heat exchanger made of V2A are included (see photos; not taken into account in the total height); some residues
Övrig information2: of previous content;bump at the insulation jacket;manhole cover plated; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1750

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.000 mm
Invändig diameter: 1.290 mm
Total höjd: 3.450 mm
Ytterdiameter: 1.540 mm

Omrörare
Kraft (kW): 7.5 / 9

Tjocklek på tank
Botten: 6 mm
Cylinder: 6 mm

Mer
Isolerad: Ja