

1750 liter tank i Syrafast 316



69 000 SEK /st exkl moms

Additional information: food colours; Cylinder can only be heated in the lower area; 1 distillation column/ heat exchanger made of stainless steel 304 is included in the scope of delivery (see photos; not included in the total height); some residues of previous content; bump at the insulation jacket; manhole cover plated
Volumetric volume (L): 1.750 L

Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 160 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 139 L

Max Overpressure: 15,40 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN150

Agitator: yes

Power: 7.5 / 9

Cylinder: 6 mm

Bottom: 6 mm

Internal diameter tank: 1.290 mm

Outer diameter tank: 1.540 mm

Cylinder height: 1.000 mm

Total height of tank: 3.450 mm

SKU: 271081



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 160 °C

Mobil tank: Nej

Övrig information: food colours; cylinder can only be heated in the lower area; 1 distillation column / heat exchanger made of V2A are included (see photos; not taken into account in the total height); some residues

Övrig information2: of previous content;bump at the insulation jacket;manhole cover plated; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1750

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 1.290 mm
Total höjd: 3.450 mm
Ytterdiameter: 1.540 mm

Omrörare

Kraft (kW): 7.5 / 9

Tjocklek på tank

Botten: 6 mm
Cylinder: 6 mm

Mer

Isolerad: Ja