

17600 liter tank i Syrafast 316



499,000,00 kr /st exkl moms

Additional information: Specified tank dimensions according to drawing; slight differences in the design of the two tanks (e.g., small dimensional deviations; nozzle positions); manhole DN 600; planned use: storage tank for WFI water

Volumetric volume (L): 17.600 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: horizontal
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside
Outlet of tank: 100
Cylinder: 9,40 mm

Bottom: 8 mm
Internal diameter tank: 2.200 mm
Outer diameter tank: 2.511 mm
Total height of tank: 3.500 mm
Total outer length: 5.160 mm

SKU: 488274

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Specified tank dimensions according to drawing; slight differences in the design of the two tanks (e.g., small dimensional deviations; nozzle positions); manhole DN 600;

planned use: storage tank

Övrig information2: for WFI water

Omrörare: Nej

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 17600

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 2.200 mm

Total höjd: 3.500 mm

Ytterdiameter: 2.511 mm

Tjocklek på tank

Botten: 8 mm

Cylinder: 9,40 mm

Mer

Isolerad: Ja