

## 17620 liter tank i Rostfritt 304



**225,000,00 kr /st exkl moms**

**Additional information:** Dairy; Manhole diameter approx. 510 mm; height-adjustable screws of the feet are no longer present; 1 small pressure point in the insulation jacket; pipe end cut flush

**Volumetric volume (L):** 17.620 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 0,50 Bar

**Max. temperature (°C):** 95 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 65

**Agitator:** yes

**Number of revolutions:** 16 / 33

**Power:** 1.2 / 2.2

**Internal diameter tank:** 2.490 mm

**Outer diameter tank:** 2.600 mm

**Cylinder height:** 3.000 mm

**Total height of tank:** 5.700 mm

**SKU:** 486287

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Dairy; Manhole diameter approx. 510 mm; height-adjustable screws of the feet are no longer present; 1 small pressure point in the insulation jacket; pipe end cut flush; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Övertryck: 0,50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 17620

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 3.000 mm

Invändig diameter: 2.490 mm

Total höjd: 5.700 mm

Ytterdiameter: 2.600 mm

**Omrörare**

Kraft (kW): 1.2 / 2.2

Varvtal: 16 / 33

**Mer**

Isolerad: Ja