

17620 liter tank i Rostfritt 304



223 000 SEK /st exkl moms

Additional information: Dairy; Manhole diameter approx. 510 mm; height-adjustable dome screws of the feet are no longer present; 1 small pressure point in the insulating jacket; pipe end cut flush

Volumetric volume (L): 17.620 L

Pressure in tank: ATM - atmospheric



Max. pressure (Bar): 0,50 Bar

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 65

Agitator: yes

Number of revolutions: 16 / 33

Power: 1.2 / 2.2

Cylinder: 4 mm

Bottom: 3,90 mm

Internal diameter tank: 2.490 mm

Outer diameter tank: 2.600 mm

Cylinder height: 3.000 mm

Total height of tank: 5.700 mm

SKU: 486287



Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Dairy; Manhole diameter approx. 510 mm; height-adjustable screws of the feet are no longer present; 1 small pressure point in the insulation jacket; pipe end cut flush; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Övertryck: 0,50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 17620

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Cylinderhöjd: 3.000 mm
Invändig diameter: 2.490 mm
Total höjd: 5.700 mm
Ytterdiameter: 2.600 mm

Omrörare

Kraft (kW): 1.2 / 2.2
Varvtal: 16 / 33

Tjocklek på tank

Botten: 3,90 mm
Cylinder: 4 mm

Mer

Isolerad: Ja