

180 liter tank i Syrafast 316



143,000,00 kr /st exkl moms

Article type: second-hand

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 180 L

Ra inner weld: 0,80

Pressure in tank: pressure and vacuum

Design pressure (Bar): -1 Bar

Max. pressure (Bar): 2 Bar



Min. pressure (Bar): -1 Bar

Max. temperature (°C): 120 °C

Min. temperature (°C): -28 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: yes

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Wall type: flat

Bottom outlet: yes

Total discharge: yes

Fixation points: 4 casters

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Water pressure HE: 6,80 Bar

Working temperature HE cylinder: 120 °C

Type of HE on the bottom: dimple-jacket

Water pressure HE: 6,80 Bar

Working temperature HE bottom: 120 °C

Heat exchanger: RVS 304

Insulation material: Mineral wool

Outer jacket (ornamental wall): RVS 304

Spray ball: RVS 316L

Valve: RVS 316L

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 316L (V4A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

CIP spray ball: yes

Max.CIP pressure (Bar): 1 Bar

Max.CIP flow (m³/h): 9

Outlet type: DIN32676

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 1750rpm

Power: 0,37

Voltage: 208-230/460 V - three-phase

Current: 1.9-1.6/0.8

Tank capacity top cylinder: 190 L

Internal diameter tank: 660 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 792 mm

Cylinder height: 457 mm

Total height of tank: 1.740 mm

Total outer width: 1.140 mm

Total outer length: 1.075 mm

Empty weight tank: 450

SKU: 304898

Mer information
