

## 185 liter tank i Syrafast 316



**119 000 SEK /st exkl moms**

**Article type:** second-hand pressure tank

**Additional information:**

The tanks have never been used.

**Volumetric volume (L):** 185 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** -1 Bar

**Max. temperature (°C):** 130 °C

**Min. temperature (°C):** -10 °C

**Material wet parts:** SS AISI 316L (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Top type:** flat

**Shape of tank:** cylindrical

**Bottom type:** dished

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** 3 non adjustable feet

**Gasket manway(s):** PTFE

**Fixation point(s):** RVS 316

**Suitable for food industry:** no

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Tank outlet:** outside Ø 65 mm

**Agitator:** no

**Top:** 38 mm

**Cylinder:** 4 mm

**Bottom:** 4 mm

**Internal diameter tank:** 502 mm

**Distance from outlet to ground:** 250 mm

**Outer diameter tank:** 670 mm

**Total height of tank:** 1.440 mm

**Total outer width:** 755,50 mm

**Total outer length:** 751,50 mm

**Empty weight tank:** 200

**SKU:** 439217

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 130 °C

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: The tanks have never been used.

Omrörare: Nej

Övertryck: 6 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dishd

Undertryck (vakuum): -1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 185



## Utrustning

Fläns för omrörare: Nej  
Märkskylt: Ja  
Tankutlopp: outside Ø 65 mm  
Teknisk ritning finns: Ja

## Översikt material

Material: Syrafast 316  
Fixeringspunkt(er): RVS 316

## Dimensioner av tank

Invändig diameter: 502 mm  
Mått utlopp till marken: 250 mm  
Total höjd: 1.440 mm  
Ytterdiameter: 670 mm

## Tjocklek på tank

Botten: 4 mm  
Cylinder: 4 mm  
Topp: 38 mm

## Mer

Isolerad: Nej  
Vikt: 200