

1850 liter tank i Rostfritt 304



228,000,00 kr /st exkl moms

Additional information: bump at the insulation jacket

Volumetric volume (L): 1.850 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 100 L

Max Overpressure: 6 Bar

Max. working temperature: 100 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: clamp

Agitator: yes

Number of revolutions: 300

Power: 1,50

Internal diameter tank: 1.178 mm

Cylinder height: 1.500 mm

Total height of tank: 3.350 mm

Empty weight tank: 850

SKU: 488058

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1850

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.178 mm
Total höjd: 3.350 mm

Omrörare

Kraft (kW): 1,50
Varvtal: 300

Mer

Isolerad: Ja
Vikt: 850