

## 1850 liter tank i Rostfritt 304



**229 000 SEK /st exkl moms**

**Additional information:** bump at the insulation jacket

**Volumetric volume (L):** 1.850 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 4 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 100 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 100 L

**Max Overpressure:** 6 Bar

**Max. working temperature:** 100 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** clamp

**Agitator:** yes

**Number of revolutions:** 300

**Power:** 1,50

**Internal diameter tank:** 1.178 mm

**Cylinder height:** 1.500 mm

**Total height of tank:** 3.350 mm

**Empty weight tank:** 850

**SKU:** 488058

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1850

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304



## Dimensioner av tank

Cylinderhöjd: 1.500 mm  
Invändig diameter: 1.178 mm  
Total höjd: 3.350 mm

## Omrörare

Kraft (kW): 1,50  
Varvtal: 300

## Mer

Isolerad: Ja  
Vikt: 850