

1850 liter tank i Syrafast 316



221 000 SEK /st exkl moms

Additional information: pharmacy; outlet fitting is missing

Volumetric volume (L): 1.850 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 100 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 100 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Number of revolutions: 300

Power: 1,50

Cylinder: 5 mm

Bottom: 6,50 mm

Internal diameter tank: 1.200 mm

Outer diameter tank: 1.350 mm

Cylinder height: 1.250 mm

Total height of tank: 3.400 mm

SKU: 270298

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: pharmacy; outlet fitting is missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1850

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.250 mm
Invändig diameter: 1.200 mm
Total höjd: 3.400 mm
Ytterdiameter: 1.350 mm

Omrörare

Kraft (kW): 1,50
Varvtal: 300

Tjocklek på tank

Botten: 6,50 mm
Cylinder: 5 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja