

## 1850 liter tank i Syrafast 316



**221 000 SEK /st exkl moms**

**Additional information:** pharmacy; outlet fitting is missing

**Volumetric volume (L):** 1.850 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 4 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 100 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 100 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 100 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 300

**Power:** 1,50

**Cylinder:** 5 mm

**Bottom:** 6,50 mm

**Internal diameter tank:** 1.200 mm

**Outer diameter tank:** 1.350 mm

**Cylinder height:** 1.250 mm

**Total height of tank:** 3.400 mm

**SKU:** 270298

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: pharmacy; outlet fitting is missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1850

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 1.250 mm  
Invändig diameter: 1.200 mm  
Total höjd: 3.400 mm  
Ytterdiameter: 1.350 mm

## Omrörare

Kraft (kW): 1,50  
Varvtal: 300

## Tjocklek på tank

Botten: 6,50 mm  
Cylinder: 5 mm

## Mer

Värmeväxlare: RVS 304  
Isolerad: Ja