

## 1855 liter tank i Syrafast 316



**174 000 SEK /st exkl moms**

**Additional information:** Pharmacy; 1 manhole diameter approx. 400 mm in the cylinder, 1 hand hole diameter approx. 250 mm in the upper bottom; 1 perforated pipe inside the lower bottom area (see photos); some residues of previous content; bump at the insulation jacket

**Volumetric volume (L):** 1.855 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 4 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 53 L

**Max Overpressure:** 6 Bar

**Max. working temperature:** 165 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** 44

**Agitator:** yes

**Number of revolutions:** 40

**Power:** 1,10

**Internal diameter tank:** 1.000 mm

**Outer diameter tank:** 1.160 mm

**Total height of tank:** 3.550 mm

**SKU:** 277918

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; 1 manhole diameter approx. 400 mm in the cylinder, 1 hand hole diameter approx. 250 mm in the upper bottom; 1 perforated pipe inside the lower bottom area (see photos) ; some residues of

Övrig information2: previous content;bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1855

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## **Dimensioner av tank**

Invändig diameter: 1.000 mm

Total höjd: 3.550 mm

Ytterdiameter: 1.160 mm

## **Omrörare**

Kraft (kW): 1,10

Varvtal: 40

## **Mer**

Värmeväxlare: RVS 304

Isolerad: Ja