1860 liter tank i Syrafast 316

122 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 2 stainless steel 304 claws (contact surface the other way round; see photos); outlet with flanged tapered section; some residues of previous content
Volumetric volume (L): 1.860 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 24 L
Max Overpressure: 16 Bar

Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN80
Agitator: yes
Number of revolutions: 177

Power: 1,10
Top: 4 mm
Cylinder: 5,20 mm
Bottom: 3,90 mm
Internal diameter tank: 990 mm

Total outer length: 3.700 mm

SKU: 397910

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); outlet with flanged taper; some residues of previous content; we can’t give any
Övrig information2: guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1860

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Invändig diameter: 990 mm

Omrörare
Kraft (kW): 1,10
Varvtal: 177

Tjocklek på tank
Botten: 3,90 mm
Cylinder: 5,20 mm
Topp: 4 mm

Mer
Isolerad: Nej