# 1860 liter tank i Syrafast 316



120 000 SEK /st exkl moms

**Additional information**: Pharmaceutical chemistry; 2 stainless steel 304 claws (contact surface the other way round; see photos); outlet with flanged tapered section; some residues of previous content
**Volumetric volume (L)**: 1.860 L
**Pressure in tank**: pressure and vacuum
**Max. pressure (Bar)**: 3,20 Bar

**Min. pressure (Bar)**: 1 Bar

**Max. temperature (°C)**: 200 °C
**Material wet parts**: SS AISI 316 (V4A)
**Model**: vertical
**Configuration**: single-skin
**Heat exchanger**: no

**Insulation**: no
**Mobile tank**: no
**Total discharge**: yes
**Volume**: 24 L
**Max Overpressure**: 16 Bar

**Max. working temperature**: 200 °C
**Type HE on the bottom**: half pipe welded onto the outside of the innertank
**Type HE on the cylinder**: half pipe welded onto the outside of the innertank
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: yes
**Flange for agitator**: no
**Outlet of tank**: flange DN80
**Agitator**: yes
**Number of revolutions**: 177

**Power**: 1,10
**Top**: 4 mm
**Cylinder**: 5,20 mm
**Bottom**: 3,90 mm
**Internal diameter tank**: 990 mm

**Total outer length**: 3.700 mm

**SKU:** 397910

# Mer information

**Beskrivning av produkt**

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); outlet with flanged taper; some residues of previous content; we can’t give any
Övrig information2: guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1860

**Utrustning**

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

**Översikt material**

Material: Syrafast 316

**Dimensioner av tank**
Invändig diameter: 990 mm

**Omrörare**
Kraft (kW): 1,10
Varvtal: 177

**Tjocklek på tank**
Botten: 3,90 mm
Cylinder: 5,20 mm
Topp: 4 mm

**Mer**
Isolerad: Nej