

## 1860 liter tank i Syrafast 316



**119 000 SEK /st exkl moms**

**Additional information:** Pharmaceutical chemistry; 2 stainless steel 304 claws (contact surface the other way round; see photos); outlet with flanged tapered section; some residues of previous content

**Volumetric volume (L):** 1.860 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 24 L

**Max Overpressure:** 16 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** flange DN80

**Agitator:** yes

**Number of revolutions:** 177

**Power:** 1,10

**Top:** 4 mm

**Cylinder:** 5,20 mm

**Bottom:** 3,90 mm

**Internal diameter tank:** 990 mm

**Total outer length:** 3.700 mm

**SKU:** 273793

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); outlet with flanged taper; some residues of previous content; we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1860

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Invändig diameter: 990 mm

## Omrörare

Kraft (kW): 1,10

Varvtal: 177

## Tjocklek på tank

Botten: 3,90 mm

Cylinder: 5,20 mm

Topp: 4 mm

## Mer

Isolerad: Nej