

1880 liter tank i Syrafast 316



265 000 SEK /st exkl moms

Additional information: Pharmacy; 1 pump (GRUNDFOS brand) is included in the scope of delivery; 1 control cabinet (used by the previous operator for 3 of these tanks) can be purchased additionally for an extra charge (see photos)

Volumetric volume (L): 1.880 L

Pressure in tank: vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 97 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 48

Agitator: yes

Number of revolutions: 329

Power: 0,75

Cylinder: 5 mm

Bottom: 10 mm

Internal diameter tank: 1.250 mm

Outer diameter tank: 1.520 mm

Cylinder height: 1.140 mm

Total height of tank: 2.600 mm

SKU: 441152

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; 1 pump (brand GRUNDFOS) is included in delivery; 1 control cabinet (used by the previous operator for 3 of these tanks) can be purchased additionally for an additional charge (see photos);

Övrig information2: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1880



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.140 mm
Invändig diameter: 1.250 mm
Total höjd: 2.600 mm
Ytterdiameter: 1.520 mm

Omrörare

Kraft (kW): 0,75
Varvtal: 329

Tjocklek på tank

Botten: 10 mm
Cylinder: 5 mm

Mer

Isolerad: Ja