1980 liter tank i Syrafast 316



113 000 SEK /st exkl moms

Additional information: Height-adjustable stainless steel 304 frame; various connections in the upper bottom; upper bottom can be moved with a lifting/swivel device, which is no longer present; agitator flange centered in the upper bottom; some residues of previous content

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Volumetric volume (L): 1.980 L
Pressure in tank: vacuum
Min. pressure (Bar): 1 Bar
Max. temperature (°C): 99 °C

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: flange
Top: 20 mm
Cylinder: 8 mm
Bottom: 8 mm

Internal diameter tank: 1.300 mm
Cylinder height: 1.095 mm
Total height of tank: 2.760 mm

SKU: 420818

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 99 °C
Mobil tank: Nej
Övrig information: Height-adjustable frame made of V2A; various connections in the upper bottom; upper bottom can be moved with a lifting/pivoting device, which is no longer available; Agitator flange centered in the
Övrig information2: upper bottom; some residues of previous content
Omrörare: Nej
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1980

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.095 mm
Invändig diameter: 1.300 mm
Total höjd: 2.760 mm

Tjocklek på tank
Botten: 8 mm
Cylinder: 8 mm
Topp: 20 mm

Mer
Isolerad: Nej