1995 liter tank i Rostfritt 304



132 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: Tank AD-2000 Merkblatt, agitator CE0344 ATEX Ex 2 1/3 G bc ; hardly ever used; we can't give any guarantees about the agitator
Volumetric volume (L): 1.995 L
Max. density P (kg/m³): 1.400
Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar
Max. temperature (°C): 90 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Configuration: single-skin

Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: dished
Total discharge: yes
Fixation points: 3 supports for platform
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304L (V2A)

Suitable for food industry: no
Documents included: yes
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

Tank outlet: inside Ø 50 mm
Agitator: yes
Position engine: at the top
Number of revolutions: 185
Power: 1,10

Voltage: 400 V - three-phase
Top: 4 mm
Cylinder: 3 mm
Bottom: 4 mm
Internal diameter tank: 1.100 mm

Outer diameter tank: 1.340 mm
Cylinder height: 2.000 mm
Total height of tank: 3.300 mm
Empty weight tank: 750

SKU: 417932

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 90 °C
Maximal densitet för produkten: 1400
Mobil tank: Nej
Övrig information: Tank AD-2000 Merkblatt, agitator CE0344 ATEX Ex 2 1/3 G bc ; hardly ever used; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 0,50 Bar
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: dished
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1995

Utrustning

Dokument finns: Ja
Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Material vätskeberörd del på omrörare: SS AISI 304L (V2A)

Dimensioner av tank
Cylinderhöjd: 2.000 mm
Invändig diameter: 1.100 mm
Total höjd: 3.300 mm
Ytterdiameter: 1.340 mm

Omrörare
Kraft (kW): 1,10
Position motor: at the top
Varvtal: 185
Spänning (Volt): 400 V – three-phase

Tjocklek på tank
Botten: 4 mm
Cylinder: 3 mm
Topp: 4 mm

Mer
Isolerad: Nej
Vikt: 750