









Construction date: 2014	
Material vessel: AISI316/AISI304	Capacity: 200 L
Workpressure: ATM.	Workpressure coil:
Maximal density: 1 kg/dm³	

C 1 : 5



Schnellmischer:
1.SRT1/0,12-750; 0,12KW; 680UPM; 400V
50/60Hz; Propeler 1x 125;
2.SRT6/0,37-1500; 0,37KW; 1410UPM; 400V
50/60Hz; Propeler 1x 100;

Item	Description	PN MPa	DN mm.	Qty.
A1	LEG ON ANCHOR PLATE (anchor bolts are not included)	-	-	3
B1	DISMOUNTABLE STATIC CIP SPRAY BALL Φ28 360° UP TO WELDING MALE NIPPLE 1/2"	atm.	1/2"	1
C1	1/2 FIXED LID	-	-	1
D1	1/2 HINGED LID	-	-	1
E1	INLET FOR AGITATOR UP TO FLANGE ∅220 s20	-	-	1
F1	TOTAL OUTLET UP TO BUTTERFLY VALVE M/M	atm.	40	1
G1	SAFETY GRID	-	-	1

Surface	Outside	2B	Welding seam	Outside	flat grinded to Ra<1.6
	Inside	2B		Inside	strip grinded to Ra<0.8

1.6	min.0,5x45°	±30'	L=1000±1	>1000 ±2 <1000 ±1

	Drawn.: S.S	Scale 1:12	Mass 70 kg	AISI 316 AISI 304	
	Checket: K.I				0.2m3
	Eng.App.:			17/07/2014	Sheet 1/1