



200 liter tank i Syrafast 316



item available on order

Article type: brand new storage tank - type VC-SLO

Additional information: Ra=<0.8µm

Capacity: 200 L

Maximal density of the product: 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Working pressure in tank: ATM - atmosferic

Max. working temperature: 80 °C

Min. working temperature: -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no



Agitator: no

Mobile tank: no

Top type: large seperat lid

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 3 non adjustable feet

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Spray ball: no

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851 female

Total outlet valve: yes, optional

Type shut-off valve: butterfly valve

Top: 2 mm

Cylinder: 3 mm

Bottom: 3 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 650 mm

Cylinder height: 625 mm

Total height of tank: 1.150 mm

Empty weight tank: 65

SKU: 7751

Additional Information



Volym i liter	200
Nyttillverkad/Begagnad	Nyttillverkad
Livsmedelsklassad	Ja
Modell	Vertikal
Material	Syrafast 316
Omrörare	Nej
Uppvärmning/kylning	Nej
Isolerad	Nej