

200 liter tank i Syrafast 316



126,000,00 kr /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-HICA

Additional information: **TYPE VC**; delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* 1 x according to drawing TANK 114 295 04; 2 x according to drawing TANK 116 010 02; Ra=<0.8µm

Volumetric volume (L): 200 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: yes

Top type: half hinging lid °

Shape of tank: cylindrical

Bottom type: conical 10 °

Total discharge: yes

Fixation points: 4 casters

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Number of sections: 1

Water pressure HE: 3 Bar

Hydraulic test pressure: 4 Bar

Contact surface cylinder: 0,75 m²

Connection HE: 1" BSP

Working temperature HE cylinder: 100 °C

Heat exchanger: RVS 304

Outer jacket (ornamental wall): RVS 304

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: yes

CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Agitator: no, optional



Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 670 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 750 mm

Cylinder height: 550 mm

Total height of tank: 1.480 mm

Empty weight tank: 130

SKU: 7313

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosfERIC

Finish rostfritt stål: 2b

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Ja

Övrig information: TYPE VC; delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);
1 x

Övrig information2: according to drawing TANK 114 295 04; 2 x according to drawing TANK 116 010 02; Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 200

Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 550 mm
Invändig diameter: 670 mm
Mått utlopp till marken: 250 mm
Total höjd: 1.480 mm
Ytterdiameter: 750 mm

Värmeväxlare

Anslutning värmeväxlare: 1" BSP
Arbetstemperatur värmeväxlare cylinder: 100 °C
Hydrauliskt provtryck botten: 4 Bar
Hydrauliskt provtryck: 4 Bar
Kontaktyta cylinder: 0,75 m²
Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Vattentryck värmeväxlare: 3 Bar

Omrörare

Kraft (kW): 0,37
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 1.410
Spänning (Volt): three-phase

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja

Vikt: 130