

200 liter tank i Syrafast 316



103 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SLA

Additional information: delivered with food certificate; *article price without agitator*; choice of 2 different types of agitators; see options; (The article can also be purchased without options); $Ra < 0.8 \mu m$

Volumetric volume (L): 200 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: half hinging lid °
Shape of tank: cylindrical
Bottom type: conical 10 °
Total discharge: yes
Fixation points: 3 non adjustable feet

Gasket manway(s): EPDM
Valve: RVS 316L
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: yes
CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm

Outlet type: 11.850
Total outlet valve: no, optional
Agitator: no, optional
Agitator type: propeller agitator
Position engine: at the top

Number of revolutions: 1.500
Power: 0,37
Voltage: 400 V - three-phase
Agitator type 2: propeller agitator

Position engine: at the top

Number of revolutions: 680

Power: 0,12

Voltage: 400 V - three-phase

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 670 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 676 mm

Cylinder height: 550 mm

Total height of tank: 1.118 mm

Empty weight tank: 70

SKU: 6251

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 200

Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: 11.850

Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304



Dimensioner av tank

Cylinderhöjd: 550 mm

Invändig diameter: 670 mm

Mått utlopp till marken: 250 mm

Total höjd: 1.118 mm

Ytterdiameter: 676 mm

Omrörare

Kraft (kW): 0,37

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 1.500

Spänning (Volt): 400 V - three-phase

Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 3 mm

Mer

Isolerad: Nej

Vikt: 70